



## M26



### Features

- Small fixed installation line array speaker
- 1.75" voice coil tweeter compression driver
- 2 high-power 6.5-inch woofers
- Horn directivity: horizontal 90° vertical 10°
- Speaker opening angle: 0-10° step: 1°
- Symmetrical design
- Three-point link hoisting
- Shell material: 18mm multilayer plywood
- Perforated iron net with mesh lining
- PU fine dot paint coverage, white can be selected

### 产品特性

- 小型固定安装线阵音箱
- 1.75英寸音圈高音压缩驱动器
- 2只高功率6.5英寸低音扬声器
- 号角指向性：水平 70° 垂直 15°
- 音箱打开角度：0-10° 步进:1°
- 对称式设计
- 三点链接吊装
- 外壳材质：18mm多层夹板
- 穿孔铁网，加网布衬里
- PU细点油漆覆盖，可选择白色


### Extended matching speakers

Stage monitor speakers: Pro120M/150M/M203  
Subwoofer:M1.8B/LA-18SUB  
Subwoofer:VT218/LA218SUB

### 扩展匹配音箱

Pro120M/150M/M203舞台监听音箱  
M1.8B/LA-18SUB超低频音箱  
VT218/LA-218SUB超低频音箱

Model 型号	M26
Nominal impedance (Passive) 标称阻抗(无源)	4 Ω
Power handling AES / Peak 额定功率/最大功率	500 W/1000W
Frequency range (-10dB) 频率范围	68 Hz - 18 kHz
Crossover Frequency 分频交叉点	1.8KHz passive
Sensitivity (1W; 1m) 灵敏度	97 dB
Max. SPL/1m peak (calc) 连续/最大声压级(计算值)	129dB/135 dB
LF transducer rated size 低音单元	2x6.5"(162mm) Cone
LF transducer voice coil diameter (低音单元音圈)	2"(49.55mm)
LF transducer magnet structure (低音单元磁体结构)	145mm ferrite 铁氧体
HF compression driver voice coil (高音驱动器音圈)	1.75"(44.4mm)Titanium 钛振膜
HF compression magnet structure (高音驱动器磁体)	120mm Ferrite 铁氧体
Enclosure material 外壳材质	18mm Plywood 多层板
Options 可选配件	Flight case 航空箱
Dimension (WxHxD) 尺寸 (宽x高x深)	560x 200 x 330 mm
Weight 重量	16 kg



## M28+M18B



### Features

- Small active line array sound system
- 3" voice coil tweeter compression driver
- 2 high-power 8-inch woofers
- Horn directivity: horizontal 90° vertical 10°
- Speaker opening angle: 0-10° step: 1°
- Symmetrical design
- Three-point link hanging
- Wooden shell: 18mm multilayer plywood
- Perforated iron net with mesh lining
- PU fine-point paint, white is optional

### 产品特性

- 小型有源线阵音响系统
- 3英寸音圈高音压缩驱动器
- 2只大功率8英寸低音扬声器
- 号角指向性：水平 80° 垂直 10°
- 音箱打开角度：0-12° 步进:1°
- 对称式设计
- 三点链接吊挂
- 木质外壳：18mm多层夹板
- 穿孔铁网，加网布衬里
- PU细点油漆，可选择白色

### Extended matching speakers

Stage monitor speakers: Pro120M/150M/M203  
Subwoofer:M1.8B/LA-18SUB /LA-21SUB  
Subwoofer:VT218/LA218SUB (2x18")

### 扩展匹配音箱

Pro120M/150M/M203舞台监听音箱  
M1.8B/LA-18SUB /LA-21SUB超低频音箱  
VT218/LA-218SUB超低频音箱

Model 型号	M28	M18B
Nominal impedance (Passive) 标称阻抗(无源)	4 Ω	8 Ω
Power handling AES / Peak 额定功率/最大功率	600 W/1200W	500 W/1000W
Frequency range (-10dB) 频率范围	72 Hz - 18 kHz	48 Hz - 200Hz
Crossover Frequency 分频交叉点	1.8KHz passive	100Hz
Sensitivity (1W; 1m) 灵敏度	98 dB	95 dB
Max. SPL/1m peak (calc) 连续/最大声压级(计算值)	112dB/128 dB	102dB/108 dB
LF transducer rated size 低音单元	2x8"(162mm) Cone	18"(450mm) Cone
LF transducer voice coil diameter (低音单元音圈)	2"(49.55mm)	4"(99.6mm)
LF transducer magnet structure (低音单元磁体结构)	145mm ferrite 铁氧体	220mm ferrite 铁氧体
HF compression driver voice coil (高音驱动器音圈)	3"(74.4mm)Titanium 钛振膜	
HF compression magnet structure (高音驱动器磁体)	170mm Ferrite 铁氧体	
Enclosure material 外壳材质	18mm Plywood 多层板	18mm Plywood 多层板
Options 可选配件	Flight case 航空箱	Flight case 航空箱
Dimension (WxHxD) 尺寸 (宽x高x深)	760x 270 x 440 mm	760x 540 x 650 mm
Weight 重量	31 kg	42 kg