


10

Ks series



Ks series is a compact multifunctional speaker series. Originated from professionalism, loyal to technology, and skilled in craftsmanship. It provides a steady stream of high boost levels and abundant output power, flexible installation methods and reliable stability. The Ks series is designed for indoor fixed installation and strives to achieve the highest standards in audio processing. The sound is clear, the timbre is balanced and the pursuit of higher product cost performance.

Ks系列是紧凑型的多功能音箱系列。源于专业，忠于科技，精于工艺，提供源源不断的高升压级和充沛的输出功率，灵活多变的安装方式和可靠的稳定性。Ks系列为室内固定安装设计，在音频处理上力求声音清晰，音色平衡并追求更高的产品性价比。



The crossover network of Ks has been carefully designed and debugged by engineers, and scientific crossover points are selected to ensure the stable operation of the driver while providing maximum output power and clear, balanced sound. The Ks series has a high-frequency overload protection circuit design, thus Reduce the chance of drive damage and improve the smooth operation of the system.

Ks的分频网络经过工程师的精心设计和调试，选择科学的分频点，在保障驱动器稳定运行的同时提供最大的输出功率和清晰平衡的声音。Ks系列具有高频信号过载电子保护电路设计，从而减少驱动器的损坏机率，提高系统运行的顺畅。



Two-Way White Utilitly

The Ks series cabinet adopts CAT KING's most mature spraying process in the past 20 years. We can provide PE/PU/polyurea spray covering technology and provide users with a white options.

两路白色实用

Ks系列箱体采用CAT KING 20年来最成熟的喷涂工艺，我们可提供PE/PU/聚脲喷涂覆盖技术，并可为用户提供白色选择。

The Ks series can be installed with 504/506 hanging pieces or fixed installation rings. It can also be used independently or in combination with a subwoofer using a standard three-point bracket. The flexible and convenient installation method meets the requirements of different places.

Ks系列可选用504/506吊件或使用吊环固定安装，也可以使用标准三点支架独立使用或和低音炮组合使用。灵活方便的安装方式满足不同场所的使用要求。

1215


Install sound



TWO-WAY PASSIVE LOUDSPEAKERS 二分频无源扬声器

Ks series is a multi-purpose two-way full-range passive speaker series, suitable for a wide range of applications. Its sound quality and compactness combine with an elegant design and accurate finishing to make the Ks series the perfect choice for any environment. Excellent acoustic performance for both background and foreground music.

Ks系列是多用途两分频全频无源扬声器系列，适用于广泛的应用。其音质和紧凑性与优雅的设计和精确的加工相结合，使Ks系列成为任何环境的完美选择。其背景音乐和前景音乐均具有出色的声学性能。



Ks1

10" passive speaker
8 Ω (+1/-1)
250W / 500W/1000W
65 Hz-18 kHz
2000Hz passive 被动
96 dB
122dB / 128dB
80° x 60°
10"(LF10140F-50)Aluminum Cone铝盆
2" (49.55mm) Kapton
140mm ferrite 铁氧体
HF100F-1.4 compression driver压缩驱动
1.4" (34.4mm) Titanium 钛金属
1" (26mm)
100mm Ferrite 铁氧体
15mm MDF 压缩板
black or White 黑色或白色细点漆
Black or White 黑色或白色穿孔网
M8 Points M8安装点
2x XLR 二个卡侬座
Φ35 mm (depth 80mm)
320 x 510 x 330mm
400 x 400 x 560mm
13 Kg / 27lbs
16 Kg / 35lbs



Ks2

12" passive speaker
8 Ω (+1/-1)
380W / 750W/1500W
60 Hz-18 kHz
1900Hz passive 被动
97 dB
123dB / 129dB
80° x 60°
12"(LF12170F-65) Aluminum Cone铝盆
2.6" (65.75mm) Kapton
170mm ferrite 铁氧体
HF120F-1.75 compression driver压缩驱动
1.75" (44.4mm) Titanium 钛金属
1" (26mm)
120mm Ferrite 铁氧体
18mm MDF 压缩板
black or White 黑色或白色细点漆
Black or White 厚黑色或白色穿孔网
M8 Points M8安装点
2x XLR 二个卡侬座
Φ35 mm (depth 80mm)
375 x 606 x 395mm
435 x 680 x 480mm
21 Kg / 46lbs
26 Kg / 57lbs



Ks5

15" passive speaker
8 Ω (+1/-1)
450W / 900W/1800W
58 Hz-18 kHz
2100Hz passive 被动
98 dB
124dB / 130dB
80° x 60°
15"(LF15190F-76)Aluminum Cone铝盆
3" (76.2mm) Kapton
190mm ferrite 铁氧体
HF120F-1.75 compression driver压缩驱动
1.75" (44.4mm) Titanium 钛金属
1" (26mm)
120mm Ferrite 铁氧体
18mm MDF 压缩板
black or White 黑色或白色细点漆
Black or White 黑色或白色穿孔网
M8 Points M8安装点
2x XLR 二个卡侬座
Φ35 mm (depth 80mm)
455 x 700 x 450mm
545 x 750 x 545mm
29 Kg / 64lbs
34 Kg / 75lbs