

E25/26/28

卓越的 "对称锥" 远程音箱

COMPACT LONG THROW LOUDSPEAKER 紧凑型远射程扬声器

The system is designed to be the perfect high output solution for live music.

该系统旨在成为长距离的现场扩声完美高输出解决方案

有针对性的设计：紧凑耐用、使用直观、易于运输，E系列扬声器的突出特点是相位锥对称设计。为满足特定场所的扩声要求，我们有设计了高性能的高频压缩驱动器和配置大功率低频驱动器。特制分频网络使它们经过压力测试。提供高功率和扩展频率响应和传输距离更远。完美适用于旅游公司和 AV 租赁公司寻找可扩展、易于部署的音频解决方案。



E28



E26



E25

SPECIFICATIONS 规格参数

MODEL

Speaker Type 音箱类型
Nominal impedance (Passive) 标称阻抗(无源)
Power RMS /Program/ Peak 额定/程序/最大功率
Frequency range (-10dB) 频率范围
Crossover Frequency (Passive) 分频点(无源)
Sensitivity (2.83 V / 1 Meter) 灵敏度 ±3dB
Max. SPL/1m peak (calc) 连续 / 最大声压级(计算值)
Horn directivity(hxv) 指向性(水平方向x垂直方向)
Low Frequency transducer 低频单元
LF transducer voice coil diameter 低音单元音圈
LF transducer magnet stucture 低音单元磁体结构
High Frequency Transducer 高频单元
HF compression driver voice coil 高音驱动器音圈
HF compression Throat diameter 高音喇叭口(直径)
HF compression magnet structure 高音驱动器磁体
Enclosure material 外壳材质
Finish(available coating) 箱体涂层
Protective grille 防护格栅
Rigging Points 安装点
Input connectors 输入连接器
Protective 碰损保护
Removable device 移动装置
Dimension (WxHxD) 净尺寸 (宽x高x深)
Dimension (WxHxD) 包装尺寸 (宽x高x深)
Weight 净重量(公斤/磅)
Weight 包装重量

2x18" Remotely speaker
4 Ω (+1/-1)
1800 W/3600W/7200W
52 Hz – 18 kHz
1300Hz passive
105 dB
133dB/139 dB
90° Round 圆型
18" (LF18220F-100)
4"(100 mm)
220mm ferrite 铁氧体
4" (HF220F-4)
4" 100mmTitanium 钛金属
1.4"(38mm)
220mm Ferrite 铁氧体
18mm plywood 多层桦木板
Polyurea black 黑色雨点
1.5mm Black grille 黑铁网
M8 Points M8安装点
2x XLR 二个卡依座
Aluminum alloy surround
4"castersx4 四只4寸脚轮
590 x 1365 x 755 mm
685 x 1440 x 850 mm
99 kg/218lbs
110 kg/242lbs

2x15" Remotely speaker
4 Ω (+1/-1)
1500 W/3000W/6000W
56 Hz – 18 kHz
1300Hz passive
102 dB
126dB/132 dB
90° Round 圆型
15" (LF15220F-100)
4"(99.6mm)
220mm ferrite 铁氧体
4"HF220F-4
4" 100mmTitanium 钛金属
1.4"(38mm)
220mm Ferrite 铁氧体
18mm plywood 多层桦木板
Polyurea black 黑色雨点漆
1.5mm Black grille 黑铁网
M8 Points M8安装点
2x XLR 二个卡依座
Aluminum alloy surround
3"castersx4 四只3寸脚轮
520 x 1195 x 675 mm
590 x 1330 x 740 mm
77 kg/170lbs
89 kg/196lbs

2x15" Remotely speaker
4 Ω (+1/-1)
1000 W/2000W/4000W
58 Hz – 18 kHz
1500KHz passive
98 dB
123dB/129 dB
90° Round 圆型
15" (LF15190F-76)
3"(76.2mm)
190mm ferrite 铁氧体
3"HF220F-3
3" 74.4mmTitanium 钛金属
1.4"(38mm)
170mm ferrite 铁氧体
18mm plywood 多层桦木板
Polyurea black 黑色雨点漆
1.5mm Black grille 黑铁网
M8 Points M8安装点
2x XLR 二个卡依座
Aluminum alloy surround
无
495 x 1060 x 655 mm
565 x 1195 x 720 mm
61 kg/134lbs
67 kg/148lbs

VERY HIGH OUT CAPABILITY
LONG-RANGE
HIGH SOUND PRESSURE LEVEL
EASY TO MOVE
STURDY AND DURABLE

REMOTELY Series

Purposeful design: rugged and usableIntuitive and easy to transport, the E-Series loudspeakers areThe outstanding feature is the symmetrical phase cone design. to satisfyFor sound reinforcement requirements in specific places, we have designshigh-performance high-frequency compression driver and configurationHigh power low frequency driver. Custom driverMake them stress-tested to deliver high powerand extended frequency response, providing high sound pressure levels andThe transmission distance is longer.Perfect for regional tour companies and AV rentalsLeasing companies looking for scalable, easy-to-deploy audiofrequency solution.

Core advantages

核心优势

Customized extra-large round horn to achieve greater frequency response and sound coverage.

特制超大型圆形号筒,最大程度的获得投射距离和声音覆盖的范围。



Different from competitors, the phase cone symmetrical design effectively improves the frequency response characteristics and electro-acoustic conversion efficiency of the speaker, achieving good linear response and being visually attractive.

与竞争对手不同,相位锥对称式设计,有效改善了音箱的频响特性和电声转换效率,在得到良好的线性反应的同时更具有视觉吸引力。



Advanced high-frequency driver installation design, this method provides better heat dissipation and easy accessory replacement

更方便的背面安装高频压缩器设计这种方法为用户提供了更快捷的配件更换服务。



CAT KING' S REVOLUTIONARY CONCEPT OF DOUBLE 15". PROVIDING FIRST-CLASS PERFORMANCE TOAN EXTENDED MARKET OF PROFESSIONAL USERS.

CAT KING革命性的音频概念兼顾实用性

PATENTED 专利产品

- Compact long range speaker
- Unique phase cone symmetrical installation design
- Special aluminum alloy strip wrapped shell
- Special large size horn technology which deliveries breathtaking results.
- The tweeter diaphragm assembly can be replaced directly on the back
- 4" Titanium Diaphragm High Frequency Compression Driver
- 15" driver for accurate low frequency response
- Install casters for easy movement
- Attractive 19-gauge perforated steel grille protects components from damage
- The back of the iron grille is combined with waterproof and dustproof professional mesh cotton

- 紧凑型的远射程扬声器
- 独特的相位锥对称安装设计
- 特殊的大型号角安装技术并带来令人惊叹的效果
- 高频振膜组件可在背部直接更换
- 4" (100mm音圈)钛振膜高频压缩驱动器
- 15"大功率驱动器(4"散热音圈)可实现准确的低音频率响应
- 特制的金属包角和铝合金条外壳包裹,避免碰损
- 底部安装脚轮,便捷移动
- 加厚穿孔钢格栅,保护组件免受损坏
- 防潮防尘的透声纤维布与格栅结合



厚积薄发: E26