

LEGENDARY SUBWOOFERS 杰出的低音炮

CAT KING subwoofers are the first choice of many sound engineers, thanks to the very high SPL levels at very low frequencies, cabinets are made of high-quality plywood with weatherproof treatments. The subs are stackable and light-weight, for easy set-up and tear down. The polyurea coating and the rugged structure of the cabinet withstand long-term use and transportation .

CAT KING低音炮是许多音响工程师的首选，这要归功于在非常低的频率下具有非常高的 SPL 水平、柜体由经过防风雨处理的优质多层胶合板制成。这些低音炮可堆叠且重量轻，易于安装和拆卸。聚脲涂层和坚固的箱体结构可承受长期使用和运输。

DOUBLE Subwoofers

Every detail of the CAT KING subwoofer has been designed and thought out with its intended use in mind. Ideal for nightclub,concert, touring or installation use.

CAT KING 低音炮的每个细节都经过专门设计和深思熟虑，并充分考虑了其预期用途。适合夜总会、音乐会、巡演或安装使用。

SPECIFICATIONS 参数

MODEL	ST218
Speaker Type 音箱类型	18"x2 Subwoofer system
Nominal impedance (Passive) 标称阻抗(无源)	4 Ω (+1/-1)
Power handling RMS / Program 额定功率/连续功率	1400 W/2800W
Frequency range (-10dB) 频率范围	45 Hz-180 Hz
Sensitivity 灵敏度	95 dB
Continuous / peak (calc) 连续 / 最大声压级(计算值)	126dB/132dB
Low Frequency transducer 低频单元	18"(450mm) LF18220F-100
Enclosure material 外壳材质	18mm Plywood 多层板
Finsh(available coating) 箱体涂层	PU black 黑色yd点
Protective grille 防护格栅	1.5mm Black perforated 黑穿孔网
Input connectors 输入连接器	2x XLR 二个卡依座
Dimension Unpacked (WxHxD) 净尺寸	1043 x 645 x 770 mm
Dimension Packed (WxHxD) 包装尺寸	700 x 1100 x 825 mm
Net Weight (Kg / lbs) 净重量(公斤/磅)	80 Kg / 176lbs
Gross Weight (Kg / lbs) 毛重量(公斤/磅)	85 Kg / 187lbs

M2.8
18"x2 Subwoofer system
4 Ω (+1/-1)
1800 W/3600W
42 Hz-180 Hz
96 dB
131dB/137dB
18"(450mm) LF18280F-125
18mm Plywood 多层hm板
PU black 黑色yd点
1.5mm Black perforated 黑穿孔网
2x XLR 二个卡依座
1298 x 565 x 805 mm
615 x 1360 x 860 mm
97 Kg / 213lbs
105 Kg / 231lbs

MODEL	VF218SUB
Speaker Type 音箱类型	18"x2 Subwoofer system
Nominal impedance (Passive) 标称阻抗(无源)	4 Ω (+1/-1)
Power handling RMS / Program 额定功率/连续功率	1800 W/3600W
Frequency range (-10dB) 频率范围	41 Hz-180 Hz
Sensitivity 灵敏度	98 dB
Continuous / peak (calc) 连续 / 最大声压级(计算值)	133dB/139dB
Low Frequency transducer 低频单元	18"(450mm) LF18280F-125
Enclosure material 外壳材质	18mm Plywood 多层板
Finsh(available coating) 箱体涂层	Durable black 黑色雨点漆
Protective grille 防护格栅	Black perforated 黑穿孔网
Input connectors 输入连接器	2x XLR 二个卡依座
Dimension Unpacked (WxHxD) 净尺寸	1298 x 565x 805 mm
Dimension Packed (WxHxD) 包装尺寸	615 x 1360 x 860 mm
Net Weight (Kg / lbs) 净重量(公斤/磅)	98 Kg / 216lbs
Gross Weight (Kg / lbs) 毛重量(公斤/磅)	106 Kg / 234lbs

U28
18"x2 Subwoofer system
4 Ω (+1/-1)
2000 W/4000W
39 Hz-180 Hz
96 dB
134dB/140dB
18"(450mm) LF18280F-125
18mm Plywood 多层板
PU black 黑色yd点
1.5mm Black perforated 黑穿孔网
2x XLR 二个卡依座
1155 x 588 x 920 mm
645 x 1215 x 975 mm
110 Kg / 243lbs
117 Kg / 258lbs

To deliver the cleanest, punchiest, and undistorted low frequencies reproduction. 提供最干净、最有力且不失真的低频再现。



ST218

- Premium 2x18" LF18220F-100 Transducers
- 100mm(4") heat dissipation voice coils
- Rugged, versatile enclosures
- Tunings available for MT/ Q amps and XCA signal processors
- Power Handling: 5600W Peak, 2800W Continuous, 1400W RMS
- Frequency Response: 45Hz-180Hz
- Max SPL: 132dB (Peak)
- Amplification options: Passive
- Dust-proof and moisture-proof net inside the grille
- 优质 2x18" LF18220F-100 换能器
- 4"(100mm) 散热音圈
- 坚固耐用的外壳
- 可用于 MT或Q系列放大器和 XCA信号处理器的调音
- 功率处理：5600W 峰值、2800W 连续、1400W 额定
- 频率响应：45Hz-180Hz
- 最大声压级：132dB (峰值)
- 放大选项：无源
- 格栅内加防潮防尘透声网



M2.8

- Premium 2x18" LF18220F-100 Transducers
- Rugged, versatile enclosures
- Tunings available for MT Q amps and XCA signal processors
- Power Handling: 7200W Peak, 3600W Continuous, 1800W RMS
- Frequency Range: 42Hz-180Hz
- Frequency Response: 47Hz-150Hz
- Max SPL: 137dB (Peak)
- Amplification options: Passive
- 2x 18" 125mm(5') inner and outer copper voice coils
- 优质 2x18" LF18280F-125 换能器
- 坚固耐用的外壳
- 可用于 MT或Q系列放大器和 XCA信号处理器的调音
- 功率处理：7200W 峰值、3600W 连续、1800W 额定
- 频率范围：42Hz-180Hz
- 频率响应：47Hz-150Hz
- 最大声压级：137dB (峰值)
- 放大选项：无源
- 2x 18" 125mm(5")内外铜音圈



VF218SUB

- Premium 2x18" LF18220F-100 Transducers
- Rugged, versatile enclosures
- Tunings available for MT Q amps and XCA signal processors
- Power Handling: 7200W Peak, 3600W Continuous,1800W RMS
- Frequency Range: 36Hz-180Hz
- Frequency Response: 41Hz-150Hz
- Max SPL: 139dB (Peak)
- Amplification options: Passive
- 2x 18' 125mm(5') inner and outer copper voice coils
- 优质 2x18" LF18280F-125 换能器
- 坚固耐用的外壳
- 可用于 MT或Q系列放大器或和 XCA信号处理器的调音
- 功率处理：7200W 峰值、3600W 连续、1800W 额定
- 频率范围：36Hz-180Hz
- 频率响应：41Hz-150Hz
- 最大声压级：139dB (峰值)
- 放大选项：无源
- 2x 18" 125mm(5")内外铜音圈



U28

- Premium 2x21" LF21280F-125 Transducers
- Rugged, versatile enclosures
- Tunings available for MT Q amps and XCA signal processors
- Power Handling: 8000W Peak, 4000W Continuous,2000W RMS
- Frequency Range: 35Hz-180Hz
- Frequency Response: 39Hz-150Hz
- Max SPL: 135dB (Peak)
- Amplification options: Passive
- 2x 21' 125mm(5') inner and outer copper voice coils
- 优质 2x21" LF21280F-125 换能器
- 坚固耐用的外壳
- 可用于 MT或Q放大器系列和 XCA信号处理器的调音
- 功率处理：8000W 峰值、4000W 连续、2000W 额定
- 频率范围：35Hz-180Hz
- 频率响应：39Hz-150Hz
- 最大声压级：135dB (峰值)
- 放大选项：无源
- 2x 21" 125mm(5")内外铜音圈